

WESGO

Data Sheet



Description:

High-purity copper, germanium and nickel alloy for vacuum brazing. Nominal composition by weight: 87.75% Cu, 12% Ge and 0.25% Ni

Prime Features:

Economical high temperature hermitic bonding

Suggested base materials:

• Copper, Kovar, Nickel, Carbon/ low alloy & Tool/high speed steel, Stainless steel, Ni-super alloys

Physical Properties*

Liquidus Temperature	975 ℃
	I 787 °F
Solidus Temperature	880 °C
	1616 °F
Coefficient of Thermal Expansion (CTE)	
Thermal Conductivity (Calculated)	24.3 W/m·K
	I4 BTU/ft·h· °F
Density	8.82 Mg/m ³
	0.318 lb/in ³
Yield Strength (0.2% offset)	117 MPa
	17.0 x 10 ³ lb/in ²
Tensile Strength	306 MPa
	44.4 x 10 ³ lb/in ²
Elongation (2in/50mm gage section)	45%
Electrical Resistivity	311 x 10-⁰ ohm m
Electrical Conductivity	3.22 x 10 ⁶ /ohm⋅m
Vapor Pressure (Calculated)	
Recommended Brazing Temperatures	1000 – 1025 °C
Recommended Brazing Atmospheres	I0⁵ mm Hg

* Please note that all values quoted are based on test pieces and may vary according to component design. These values are not guaranteed in any way and should only be treated as indicative values. They should be used for guidance only and for no other purpose whatsoever.

Impurity Limits

Zn	less than 0.001%	All other metallic impurities hav higher than 10 ⁷ mm Hg at 500 0.002% each. Impurities having lower than 10 ⁷ mm Hg at 500 total of 0.075%. (This applies to powder and extrudable paste.)
Cd	less than 0.001%	
РЬ	less than 0.002%	
Р	less than 0.002%	
С	less than 0.01%	

r metallic impurities having a vapor pressure han 10⁻⁷ mm Hg at 500 °C are limited to each. Impurities having a vapor pressure nan 10⁻⁷ mm Hg at 500 °C are limited to a 0.075%. (This applies to all forms except

Supplied As:

- Foil • Wire
- Powder
- Extrudable paste
- Preforms
- The determination as to the adaptability of any Wesgo materials to the specific needs of the Buyer is solely the Buyer's prerogative and responsibility. All technical information, data and recommendations are based on tests and accumulated experience data, which Wesgo believed to be reliable. However, the accuracy and completeness thereof are not guaranteed.



www.morganbrazealloys.com Morgan Advanced Materials, 2425 Whipple Road, Hayward CA 94544 Contact: +1 510 491 1100 | Certifications: AS9100D, ISO9001:2015, ISO14001:2015



Morgan Advanced Materials PLC Registered in England & Wales at Quadrant, 55-57 High Street, Windsor, Berkshire SL4 1LP UK Company No. 286773 ©Copyright of The Morgan Advanced Materials PLC and its affiliates, 06/2018. All rights reserved.